

# MATERIAL SAFETY DATA SHEET

Page 1 of 6  
Diamond Gloss Satin for PS  
Part No. 10196Z Aerosol  
Revision 1 ~ February 9, 2006

## EMERGENCY OVERVIEW

**CONTENTS EXTREMELY FLAMMABLE AND UNDER PRESSURE. STORE BELOW 120°F, OUT OF SUNLIGHT, AND AWAY FROM HEAT SOURCES. DO NOT PUNCTURE OR INCINERATE. AVOID CONTACT WITH SKIN AND EYES. VAPOR HARMFUL. HARMFUL OR FATAL IF SWALLOWED. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.**

## SECTION 1 CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

<b>MANUFACTURED FOR:</b>	<i>The Easthill Group dba/ The Eastwood Co. 263 Shoemaker Rd. Pottstown, PA 19464</i>	<b>SUPPLIER:</b>	<i>The Easthill Group, Inc. 263 Shoemaker Road Pottstown PA 19464 USA</i>
<b>INFORMATION:</b>	<i>USA &amp; Canada: 1-800-345-1178 Outside USA: (610) 323-2200</i>	<b>INFORMATION:</b>	<i>610-323-2200</i>
<b>EMERGENCY:</b>	<i>Chem-Trec 1-800-424-9300</i>	<b>SUPPLIER 24hr:</b>	<i>1-800-424-9300</i>
<b>PRODUCT NUMBER:</b>	<i>10196Z</i>	<b>SUPPLIER NUMBER:</b>	<i>10196Z</i>
<b>PRODUCT DESCRIPTION:</b>	<i>Diamond Clear Gloss for Painted Surfaces</i>		
<b>PRODUCT TYPE:</b>	<i>Aerosol</i>	<b>REVISION NUMBER:</b>	<i>1</i>
<b>CAS NUMBER:</b>	<i>Mixture</i>	<b>REVISION DATE:</b>	<i>February 9, 2006</i>
		<b>PRINT DATE:</b>	<i>February 9, 2006</i>
		<b>PREPARED BY:</b>	<i>Safety &amp; Environmental Manager</i>

## SECTION 2 COMPOSITION / INFORMATION ON INGREDIENTS

INGREDIENT	CAS NUMBER	OSHA PEL	NIOSH REL	ACGIH PEL	IDLH	% WT
<i>Oxibismethane</i>	<i>000115-10-6</i>	<i>N/E</i>	<i>N/E</i>	<i>N/E</i>	<i>N/E</i>	<i>30-40</i>
<i>n-Hexane</i>	<i>000110-54-3</i>	<i>500 ppm</i>	<i>50 ppm</i>	<i>50 ppm</i>	<i>1100 ppm</i>	<i>10-20</i>
<i>Xylene</i>	<i>001330-20-7</i>	<i>100 ppm</i>	<i>100 ppm</i>	<i>100 ppm</i>	<i>900 ppm</i>	<i>10-20</i>
<i>Light Aliphatic Petroleum Solvent Naphtha</i>	<i>064742-89-8</i>	<i>N/E</i>	<i>N/E</i>	<i>N/E</i>	<i>N/E</i>	<i>10-20</i>
<i>Ligroine</i>	<i>008032-32-4</i>	<i>N/E</i>	<i>350 mg/m3</i>	<i>300 ppm</i>	<i>N/E</i>	<i>&lt; 10</i>
<i>Acetone</i>	<i>000067-64-1</i>	<i>1000 ppm</i>	<i>250 ppm</i>	<i>500 ppm</i>	<i>750 ppm</i>	<i>&lt; 10</i>
<i>Liquefied Petroleum Gas</i>	<i>068476-85-7</i>	<i>1000 ppm</i>	<i>1000 ppm</i>	<i>1000 ppm</i>	<i>2000 ppm</i>	<i>&lt; 10</i>

See Section 11 for LD50 and LC50 Species/Route Information.

See Sections 15 and 16 for Symbol Letters and R Phases.

## SECTION 3 HAZARD IDENTIFICATION

### ROUTES OF ENTRY:

Skin Contact	<input checked="" type="checkbox"/>	Skin Absorption	<input checked="" type="checkbox"/>	Eye Contact	<input checked="" type="checkbox"/>	Inhalation	<input checked="" type="checkbox"/>	Ingestion	<input type="checkbox"/>
--------------	-------------------------------------	-----------------	-------------------------------------	-------------	-------------------------------------	------------	-------------------------------------	-----------	--------------------------

### EFFECTS OF ACUTE EXPOSURE

**EYE:** *Liquid contact may cause pain along with moderate eye irritation.*

**SKIN:** *Prolonged or repeated exposure may cause skin irritation. Repeated contact may cause drying or flaking of skin. May cause more severe response if confined to skin.*

**INGESTION:** *Due to being an aerosol, the product does not lend itself to ingestion. Should ingestion occur, it may cause irritation to membranes of the mouth, throat, and gastrointestinal tract resulting in vomiting and/or cramps. Aspiration of vomit into the lungs may cause inflammation, and possible chemical pneumonitis, bronchopneumonia, or pulmonary edema.*

**INHALATION:** *Prolonged or repeated overexposure is anesthetic. May cause irritation of the respiratory tract, or acute nervous system depression characterized by headache, dizziness, staggering gait, confusion or death. Irritation of the mucous membranes, coughing, and dyspnoea are also possible.*

### OTHER HEALTH HAZARD DATA

**EFFECTS OF CHRONIC EXPOSURE:** *Reports have associated repeated and prolonged occupational overexposure to solvents with irreversible brain and nervous system damage (sometimes referred to as "Solvent or Painter's Syndrome"). Intentional misuse by deliberately concentrating and inhaling this product may be harmful or fatal.*

# MATERIAL SAFETY DATA SHEET

Page 2 of 6  
Diamond Gloss Satin for PS  
Part No. 10196Z Aerosol  
Revision 1 ~ February 9, 2006

*n-Hexane is toxic to the peripheral nerves, characterized by numbness, tingling, or pain in the extremities, progressively worsening of neuromuscular motor coordination (polyneuritis or polyneuropathy), and even partial paralysis.*

**MEDICAL CONDITIONS AGGRAVATED:** May aggravate personnel with pre-existing disorders associated with any of the Target Organs.

**PRIMARY HAZARDS:** Sensory Irritation (xylene, ligroine, acetone), Neuropathy (n-hexane).

**CARCINOGEN DATA:** Ethyl Benzene (a component of Xylene) is listed with IARC as Class 2B (possible human carcinogen) and with ACGIH as A3 (confirmed animal carcinogen with unknown relevance to humans). Ethyl Benzene is also listed with the State of California as a carcinogen.

**CALIFORNIA PROP 65 WARNING:** This product contains a substance known to the State of California to cause cancer.

**TARGET ORGANS:** Eyes, skin, respiratory system, central nervous system, peripheral nervous system

## OSHA HAZARD CLASSIFICATIONS

HEALTH HAZARD CLASSIFICATION				PHYSICAL HAZARD CLASSIFICATION					
Irritant	<input checked="" type="checkbox"/>	Sensitizer	<input checked="" type="checkbox"/>	Combustible	<input type="checkbox"/>	Explosive	<input type="checkbox"/>	Pyrophoric	<input type="checkbox"/>
Toxic	<input checked="" type="checkbox"/>	Highly Toxic	<input type="checkbox"/>	Flammable	<input checked="" type="checkbox"/>	Oxidizer	<input type="checkbox"/>	Water Reactive	<input type="checkbox"/>
Corrosive	<input type="checkbox"/>	Carcinogenic	<input type="checkbox"/>	Compressed Gas	<input checked="" type="checkbox"/>	Organic Peroxide	<input type="checkbox"/>	Unstable	<input type="checkbox"/>

## SECTION 4 FIRST AID MEASURES

**INGESTION:** Do not induce vomiting! Immediately have the victim drink plenty of water. Do not give milk or digestible oils. Keep airways free. Contact a physician. Never give anything by mouth if victim is rapidly losing consciousness, unconscious, or convulsing.

**SKIN:** Remove with soap and water. Consult a physician if irritation continues. If large skin area is affected, remove contaminated clothing.

**EYE:** Immediately flush with plenty of clear water for at least 15 minutes. Make sure to flush under the eyelids. Consult a physician.

**INHALATION:** Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek medical attention if symptoms persist or if unconscious.

**NOTES TO PHYSICIAN:** Epinephrine and other sympathomimetic drugs may initiate cardiac arrhythmias (irregular beating) in persons exposed to high concentrations of n-Hexane. If used, monitor heart activity closely.

## SECTION 5 FIRE FIGHTING MEASURES

**CONDITIONS OF FLAMMABILITY:** Heat, sparks, flame, red hot metal

**SUITABLE MEANS OF EXTINCTION:** Water, CO<sub>2</sub>, dry chemical, or universal aqueous film forming foam.

**UNSUITABLE EXTINGUISHING MEDIA:** N/Av

**FLASH POINT AND METHOD OF DETERMINATION:** Propellant < 0 F, Tagged Closed Cup

**FLAMMABLE LIMITS:** Lower (LEL): 1.8% @ 25 C Upper (UEL): 9.5% @ 25 C

**AUTOIGNITION TEMPERATURE:** N/Av

**HAZARDOUS COMBUSTION PRODUCTS:** Oxides of Carbon (CO, CO<sub>2</sub>), smoke, and vapors as products of incomplete combustion.

**EXPLOSION DATA - SENSITIVITY TO MECHANICAL IMPACT:** N/Av

**EXPLOSION DATA - SENSITIVITY TO STATIC DISCHARGE:** N/Av

**SPECIAL FIRE FIGHTING PROCEDURES:** Use water spray to cool fire exposed aerosol containers, as contents can rupture violently from heat developed pressure. Firemen should wear self-contained breathing apparatus.

**SPECIAL FIRE AND EXPLOSION HAZARDS:** Contents extremely flammable and under pressure.

## SECTION 6 ACCIDENTAL RELEASE MEASURES

**CONTAINMENT PROCEDURES:** Product is an aerosol, therefore spills and leaks are unlikely. In case of rupture, released content should be contained as any other solvent spill.

**SPILL CLEANUP:** Spills from aerosol cans are unlikely and are generally of small volume. Large spills are therefore not normally considered a problem. In case of actual rupture, avoid breathing vapors and ventilate area well. Remove sources of ignition and use non-sparking equipment. Soak up material with inert absorbent and place in safety containers for proper disposal.

**SPECIAL INSTRUCTIONS:** Aerosol products represent a limited hazard and will not spill or leak unless ruptured. In case of rupture contents are generally evacuated from the can rapidly. Area should be ventilated immediately and continuous ventilate provided until all fumes and vapors have been removed. Aerosol cans should never be incinerated or burned. See Section 13 for disposal.

**REPORTING REQUIREMENTS:** Spills due to the rupture of a single aerosol can are generally below any regulatory reporting requirements. However, if larger spills somehow result, the reporting requirements of all governing agencies should be observed.

# MATERIAL SAFETY DATA SHEET

Page 3 of 6  
Diamond Gloss Satin for PS  
Part No. 10196Z Aerosol  
Revision 1 ~ February 9, 2006

## SECTION 7 HANDLING AND STORAGE

**HANDLING:** Avoid prolonged or repeated skin contact. Avoid breathing of vapors. Do not incinerate (burn) containers. Always replace overcap when not in use.

**STORAGE:** Storage of individual cans should be done in an area below 120F, and away from heat sources. Ensure can is in a secure place to prevent knocking over and accidental rupture. For storage of pallet quantities, compliance with NFPA 30B (Manufacture and Storage of Aerosol Products) is recommended. This product is classified as a Level 1 Aerosol.

## SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

**EXPOSURE LIMIT VALUES:** Since this product is a mixture, an exposure value is not available. In determination of any exposure procedures, protection, or testing, use the lowest rated ingredient from Section 2.

**ENGINEERING AND EXPOSURE CONTROLS:** General ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Local exhaust ventilation or an enclosed handling system may be necessary to control air contamination below that of the lowest PEL rated ingredient from Section 2.

**RESPIRATORY PROTECTION:** A NIOSH approved respirator with an organic vapor cartridge may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. If respirators are needed, compliance with OSHA standard 29 CFR 1910.134 is necessary within the United States.

**SKIN AND HAND PROTECTION:** For brief contact, no precautions other than clean body-covering clothing should be needed. When prolonged or repeated contact could occur, use protective clothing impervious to the ingredients listed in Section 2.

**EYE PROTECTION:** Safety glasses with side shields are recommended as a minimum for any type of industrial chemical handling. Where eye contact with this material could occur, chemical splash proof goggles are recommended.

## SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

<b>BOILING POINT:</b> . . . . .	N/D	<b>MELTING/FREEZING POINT:</b> . . .	N/D
<b>SPECIFIC GRAVITY (H<sub>2</sub>O=1):</b> . . .	0.742 g/cc	<b>COEFF. OF WATER/OIL DIST.:</b> . . .	N/D
<b>VAPOR PRESSURE:</b> . . . . .	Approx 70 psig	<b>pH:</b> . . . . .	Neutral
<b>VAPOR DENSITY:</b> . . . . .	N/D	<b>EVAPORATION RATE:</b> . . . . .	Rapid
<b>PHYSICAL STATE:</b> . . . . .	Liquid Under Pressure	<b>WATER SOLUBILITY:</b> . . . . .	N/D
<b>PERCENT VOLATILE:</b> . . . . .	93% Wt (91% Vol) Max	<b>VOLATILITY:</b> . . . . .	5.116 lbs/gal (0.614 g/cc)
<b>PERCENT VOC:</b> . . . . .	86% Wt (88% Vol) Max	<b>MIR VALUE:</b> . . . . .	1.788
<b>VISCOSITY:</b> . . . . .	N/D	<b>ODOR THRESHOLD:</b> . . . . .	N/D
<b>APPEARANCE:</b> . . . . .	Clear Liquid	<b>ODOR:</b> . . . . .	Slight

## SECTION 10 STABILITY AND REACTIVITY

**CONDITIONS OF INSTABILITY:** . N/Av

**STABILITY:** . . . . . Stable

**HAZARD POLYMERIZATION:** . . Not expected to occur

**MATERIAL INCOMPATIBILITY:** . Strong oxidizers, nitrates, alkalis, acids, chlorine, fluorine, powdered metal salts

**CONDITIONS OF REACTIVITY:** . Heat, sparks, flame, red hot metal

**DECOMPOSITION PRODUCTS:** Oxides of carbon.

## SECTION 11 TOXICOLOGICAL INFORMATION

### LD50 AND LC50 SPECIES/ROUTE INFORMATION:

INGREDIENT	ORAL LD50	DERMAL LD50	INHALATION LC50
Oxibismethane	N/Av	N/Av	164 mg/l /4hr, rat
n-Hexane	28710 mg/kg, rat	>2000 mg/kg, rabbit	48000 ppm /4hr, rat
Xylene	2840 mg/kg, rat	4500 mg/kg, rabbit	6300 mg/l /4hr, rat
Light Aliphatic Petroleum Solvent Naphtha	N/Av	N/Av	N/Av
Ligroine	N/Av	N/Av	3400 ppm /4hr, rat
Acetone	5800 mg/kg, rat	20000 mg/kg, rabbit	76 mg/m <sup>3</sup> /4hr, rat
Liquefied Petroleum Gas	N/Av	N/Av	57.42% v/v, mice

**IRRITANCY OF PRODUCT:** . . . . The following ingredients are considered eye irritants: Acetone. Skin irritants: Xylene, n-Hexane.

**SENSITIZATION TO PRODUCT:** The following ingredients are considered sensitizers: n-Hexane.

**REPRODUCTIVE TOXICITY:** . . . The European Union claims n-Hexane carries a possible risk of impaired fertility.

**TERATOGENICITY:** . . . . . N/Av

# MATERIAL SAFETY DATA SHEET

Page 4 of 6  
Diamond Gloss Satin for PS  
Part No. 10196Z Aerosol  
Revision 1 ~ February 9, 2006

MUTAGENICITY: ..... N/Av  
SYNERGISTIC PRODUCTS: ... N/Av

## SECTION 12 ECOLOGICAL INFORMATION

### ECOTOXICITY:

INGREDIENT	FISH LC50	DAPHNIA EC50	ALGAL IC50	BACTERIAL EC50
Oxibismethane	N/Av	N/Av	N/Av	N/Av
n-Hexane	4 mg/l /24 hr	2.1 mg/l /48 hr	1079 mg/l /96 hr	N/Av
Xylene	14 mg/l /96 hr	165 mg/l /24 hr	N/Av	N/Av
Light Aliphatic Petroleum Solvent Naphtha	N/Av	N/Av	N/Av	N/Av
Ligroine	N/Av	N/Av	N/Av	N/Av
Acetone	8300 mg/l /96 hr	12600 mg/l /48 hr	7500 mg/l /8 day	530 mg/l /8 day
Liquefied Petroleum Gas	N/Av	N/Av	N/Av	N/Av

MOBILITY: ..... N/Av

PERSISTANCE: ..... N/Av

DEGRADIBILITY: ..... N/Av

BIOACCUMULATION: ..... N/Av

OTHER ECOLOGIC DATA: .... Do not allow to enter waters, waste water, or soil. N-Hexane is toxic to aquatic organisms and may cause long-term adverse effects in the aquatic environment.

EFFECT ON OZONE LAYER: .. This product does not contain any ozone depleting ingredients.

## SECTION 13 DISPOSAL CONSIDERATIONS

Hazard characteristics and regulatory waste stream classification can change with product use and location. Accordingly, it is the responsibility of the user to determine the proper storage, transportation, treatment, and/or disposal methodologies for spent materials and residues at the time of disposition. All waste material must be disposed of in compliance with the respective national, federal, state, and/or local regulations.

In the United States, an aerosol container that does not contain a significant amount of liquid would meet the definition of scrap metal (40 CFR 261.1(c)(6)), and would be exempt from RCRA regulation under 40 CFR 261.6(a)(3)(iv) if it is to be recycled. If containers are to be disposed of (not recycled) it must be managed under all applicable RCRA and state regulations.

## SECTION 14 TRANSPORTATION INFORMATION

### DOT SHIPPING INFORMATION (United States)

PROPER SHIPPING NAME: . Consumer Commodity

HAZARD CLASS: ..... ORM-D

PACKAGING GROUP: ..... None

UN or ID NUMBER: ..... None

### TDG SHIPPING INFORMATION (Canada)

PROPER SHIPPING NAME: . Aerosols, Flammable Ltd Qty

HAZARD CLASS: ..... 2.1

PACKAGING GROUP: ..... -

UN or ID NUMBER: ..... UN1950

### IMDG SHIPPING INFORMATION (International Ocean)

PROPER SHIPPING NAME: . Aerosols, Limited Quantity

CLASS: ..... 2

PACKAGING GROUP: ..... -

SUBSIDIARY RISK(S): ..... -

UN or ID NUMBER: ..... UN1950

PACKING INSTRUCTIONS: . P003

EmS NO.: ..... F-D, S-U

STOWAGE: ..... Category A

MFAG NO.: ..... 620

### ICAO/IATA SHIPPING INFORMATION (International Air)

PROPER SHIPPING NAME: Consumer Commodity

HAZARD CLASS: ..... 9

PACKAGING GROUP: ..... None

UN or ID NUMBER: ..... ID8000

### ADR SHIPPING INFORMATION (European Union)

PROPER SHIPPING NAME: Aerosols, Limited Quantity

ADR CLASS: ..... 2

PACKAGING GROUP: ..... -

UN or ID NUMBER: ..... UN1950

CLASSIFICATION CODE: . LQ1

HAZARD ID NO.: ..... -

### NMFC DESCRIPTION (United States)

ITEM DESCRIPTION: ..... Compounds, Lubricating

ITEM NO.: ..... 50303

CLASS: ..... 55

### NORTH AMERICAN EMERGENCY RESPONSE GUIDE

ID NUMBER: ..... 8000

GUIDE NUMBER: ..... 171

# MATERIAL SAFETY DATA SHEET

Page 5 of 6  
Diamond Gloss Satin for PS  
Part No. 10196Z Aerosol  
Revision 1 ~ February 9, 2006

## SECTION 15 REGULATORY INFORMATION

### UNITED STATES - FEDERAL:

INGREDIENT	CAS NO	TSCA	RCRA	CERCLA	SARA 313	CAA	CWA
Oxibismethane	115-10-6	<b>T</b>					
n-Hexane	110-54-3	<b>T</b>		5000#	15 %	XOV	100#
Xylene	1330-20-7	<b>T</b>	U239	100#	12 %	XOV	100#
Light Aliphatic Petroleum Solvent Naphtha	64742-89-8	<b>T</b>					
Ligroine	8032-32-4	<b>T</b>					
Acetone	67-64-1	<b>T</b>	U002	5000#			
Liquefied Petroleum Gas	68476-85-7	<b>T</b>					

### UNITED STATES - STATES:

INGREDIENT	CA	DE	FL	MA	PA	MN	NJ	NY	WA
Oxibismethane			<b>T</b>	5,6		I	<b>T</b>		
n-Hexane		<b>T</b>	<b>T</b>	2,4,5,6		ANO	<b>T</b>	<b>T</b>	<b>T</b>
Xylene	C*	<b>T</b>	<b>T</b>	2,4,F8 F9	E	ANO	<b>T</b>	<b>T</b>	<b>T</b>
Light Aliphatic Petroleum Solvent Naphtha									
Ligroine									<b>T</b>
Acetone		<b>T</b>	<b>T</b>	2,4,5,6 F8 F9	E	ANO	<b>T</b>	<b>T</b>	<b>T</b>
Liquefied Petroleum Gas									

\*CA-Xylene is not listed on Prop-65 as a carcinogen but Ethyl Benzene, a component of xylene, is listed.

### CANADA:

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

All of the components in this product are listed on the Domestic Substances List (DSL).

**WHMIS Classification:** A, B5, D2A, D2B


### EUROPEAN UNION:

INGREDIENT	EINECS	SYMBOL	RISK PHRASES	SAFETY PHRASES
Oxibismethane	204-065-8	F	12	2-9-16-33
n-Hexane	203-777-6	F Xn Xi N	11-38-48/20-51/53-62-65-67	2-9-16-29-33-36/37-61-62
Xylene	215-535-7	F Xn	10-20/21-38	2/25
Light Aliphatic Petroleum Solvent Naphtha	265-192-2			2-23-24-62
Ligroine	232-453-7	T Xn	45-65	45-53
Acetone	200-662-2	F Xi	11-36-66-67	2-9-16-26
Liquefied Petroleum Gas	270-704-2	F+	12	2-9-16-33

## SECTION 16 OTHER INFORMATION



Canadian Hazard Symbols



European Hazard Symbols

### HMIS and NFPA RATINGS:

	HEALTH	FLAMMABILITY	REACTIVITY	SPECIAL
HMIS RATING	1	4	0	B
NFPA RATING	1	4	0	-

### R and S PHASES (European Union):

CODE	RISK or SAFETY PHRASE
R12	Extremely Flammable
R20/21	Harmful by inhalation and in contact with skin
R36/38	Irritating to eyes and skin
R45	May cause cancer
R48/20	Danger of serious damage to health by prolonged exposure through inhalation

# MATERIAL SAFETY DATA SHEET

Page 6 of 6  
Diamond Gloss Satin for PS  
Part No. 10196Z Aerosol  
Revision 1 ~ February 9, 2006

CODE	RISK or SAFETY PHRASE
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment
R62	Possible risk of impaired fertility
R65	May cause lung damage if swallowed
R66	Repeated exposure may cause skin dryness or cracking
R67	Vapours may cause drowsiness and dizziness
S2	Keep out of the reach of children
S16	Keep away from sources of ignition - No smoking
S24/25	Avoid contact with skin and eyes
S26	In case of contact with eyes, rinse immediately with plenty of water and seek medical attention
S29	Do not empty into drains
S33	Take precautionary measures against static discharges
S36/37	Wear suitable protective clothing and gloves
S45	In case of accident or if you feel unwell, seek medical advice immediately
S61	Avoid release to the environment.
S62	If swallowed do not induce vomiting, seek medical advice immediately

#### DISCLAIMER OF LIABILITY:

The information contained herein is based upon data provided to us by our suppliers, and reflects our best judgement. However, no warranty of merchantability, fitness for any use, or any other warranty or guarantee is expressed or implied regarding the accuracy of such data, or the results to be obtained from use thereof. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, we do not assume any responsibility for the results of such application. This information is furnished upon the condition that the persons receiving it shall make their own determinations of the suitability of the material for any particular purpose.

#### REVISIONS:

Revision 1 - 02/09/2006 ..... Original