



# EXTREME CHASSIS BLACK<sup>®</sup> SATIN

Part #11176ZP

**3X MORE DURABLE**  
than Original Chassis Black<sup>®</sup>

Average Coverage: 40 sq. ft.

**DANGER!** FLAMMABLE LIQUID AND VAPOR. Vapor May Cause Flash Fire. Harmful or Fatal if Swallowed. Vapor Harmful. Irritating To Skin and Eyes. Read Precautions On Rear Panel Before Use.

1 US Quart (.496 liter)

## DIRECTIONS

1. Surface must be clean and dry before painting. Use Eastwood's PRE Painting Prep to remove residual grease and oil. Can be used on bare metal or over a primer. For increased durability, prime with Extreme Chassis Black<sup>®</sup> Primer Quart (11194ZP), wait 15 minutes to 1 hour and topcoat with Extreme Chassis Black<sup>®</sup>. Do not use over self-etching primers. Test for compatibility if not using over Extreme Chassis Black<sup>®</sup> Primer. For best results, use when can and room temperature are between 70° to 90° F at 50% or less humidity.
2. Stir for at least 1 minute before use.
3. For Spray-on Application: several light coats give a better finish than one heavy coat. Contents are thinned to sprayable consistency. If desired, further thin with Toluol or Xylol. Apply only enough paint to achieve full hiding. For faster cure, apply a maximum of 2 coats primer and 2 coats Extreme Chassis Black<sup>®</sup>. Allow 24 hours between coats.
4. Finished article should be allowed to dry 48-72 hours before being handled.

**CONTAINS:** Stoddard Solvent 8052-41-3, Acetone 67-64-1, Xylene 1330-20-7, and Carbon Black 1333-86-4.

**DANGER: FLAMMABLE LIQUID AND VAPOR.** Keep away from heat, sparks and flames. Do not store above 120°F. Harmful or fatal if swallowed. Vapor harmful. Use only with adequate ventilation. Avoid contact with eyes and prolonged or repeated contact with skin.

**FIRST AID:** In case of eye contact, flush thoroughly with water for 15 minutes and get medical attention. For skin contact, wash with soap and water. If overcome by vapors, remove to fresh air. If swallowed, do not induce vomiting, contact physician immediately.

**WARNING:** This product contains chemicals known to the State of California to cause cancer.

## KEEP OUT OF REACH OF CHILDREN

For spills, leaks, fire, or exposure call day or night:  
CHEMTREC 1-800-424-9300 (USA toll-free) (202) 483-7616 (Intl.-collect)

Manufactured for The Eastwood Company 263 Shoemaker Rd, Pottstown, PA 19464  
USA: 1-800-345-1178 • Canada: 1-800-820-9042 International: (610) 323-2200  
www.eastwood.com

