

Printing date 26.08.2010 Revision: 26.08.2010

## 1 Identification of the substance/preparation and of the company/undertaking

· Product details

· Trade name: Dinitrol 6085 Faserfeinspachtel hell

· Application of the substance / the preparation Knife filler/ Surfacer

· Manufacturer/Supplier:

 $Dinol\ GmbH$ 

Pyrmonter Strasse 76

D-32676 Lügde

*Tel:* +49 5281 9829 80 *Fax:* +49 5281 9829 860

E-mail: thomas.suerig @dinol.com

- · Further information obtainable from: Research & Development
- · Information in case of emergency: Giftnotruf Berlin +49(0)30 30686 790 Beratung in Deutsch und Englisch.

### 2 Hazards identification

· Hazard description:



Xn Harmful

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

R 10 Flammable.

R 20 Harmful by inhalation.

R 36/38 Irritating to eyes and skin.

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

## 3 Composition/information on ingredients

- · Chemical characterization
- · **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:				
CAS: 100-42-5 EINECS: 202-851-5	•	<b>X</b> Xn, <b>X</b> Xi; R 10-20-36/38	10-<25%	
	Polyamine amide salt	Xi, ₩ N; R 38-51/53	<1%	

· Additional information: For the wording of the listed risk phrases refer to section 16.

### 4 First-aid measures

· General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Call a doctor immediately.

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. In case of unconsciousness place patient stably in side position for transportation.

· After skin contact: Immediately wash with water and soap and rinse thoroughly.

(Contd. on page 2)



Printing date 26.08.2010 Revision: 26.08.2010

Trade name: Dinitrol 6085 Faserfeinspachtel hell

(Contd. of page 1)

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Do not induce vomiting; call for medical help immediately.
- · Information for doctor:
- · The following symptoms may occur:

Nausea

Dizziness

Headache

5 Fire-fighting measures

- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents:

Water

Water with full jet

· Special hazards caused by the substance, its products of combustion or resulting gases:

Carbon monoxide (CO)

Under certain fire conditions, traces of other toxic gases cannot be excluded.

- · Protective equipment: Mount respiratory protective device.
- · Additional information

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

#### 6 Accidental release measures

- · Person-related safety precautions: Wear protective equipment. Keep unprotected persons away.
- · Measures for environmental protection: Do not allow to enter sewers/ surface or ground water.
- · Measures for cleaning/collecting:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

### 7 Handling and storage

- · Handling:
- · Information for safe handling:

No special measures required.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.

GB



Printing date 26.08.2010 Revision: 26.08.2010

Trade name: Dinitrol 6085 Faserfeinspachtel hell

(Contd. of page 2)

## 8 Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · Ingredients with limit values that require monitoring at the workplace:

100-42-5 Styrene (10-<25%)

WEL Short-term value: 1080 mg/m³, 250 ppm Long-term value: 430 mg/m³, 100 ppm

- · Additional information: The lists valid during the making were used as basis.
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· For the permanent contact in work areas without heightened risk of injury (e.g. Laboratory) gloves made of the following material are suitable:

Nitrile rubber

Neoprene gloves (0,47 mm)

· For the permanent contact gloves made of the following materials are suitable:

Nitrile rubber

Neoprene gloves (0,47 mm)

· For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable: Neoprene gloves (0,47 mm)

Nitrile rubber

- · As protection from splashes gloves made of the following materials are suitable: Nitrile rubber
- · Not suitable are gloves made of the following materials: Strong material gloves
- · Eye protection:



Tightly sealed goggles

· **Body protection:** Protective work clothing



Printing date 26.08.2010 Revision: 26.08.2010

Trade name: Dinitrol 6085 Faserfeinspachtel hell

(Contd. of page 3)

General Information	
Form:	Pasty
Colour:	Whitish
Odour:	Characteristic
Change in condition	
Melting point/Melting range.	Undetermined.
Boiling point/Boiling range:	145°C
Flash point:	31°C
Ignition temperature:	480°C
Self-igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtur are possible.
Explosion limits:	
Lower:	1.2 Vol %
Upper:	8.9 Vol %
Vapour pressure At 20°C:	6 hPa
Density At 20°C:	1.7 g/cm³ (DIN 51757)
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Viscosity:	
Dynamic At 20°C:	11000 mPas
Solvent content:	
Organic solvents:	17.0 %
Solids content:	80.6 % (DIN 53216)

## 10 Stability and reactivity

· Additional information:

*VOC (EU): VOC (EU):* 

- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Materials to be avoided:
- · Dangerous reactions No dangerous reactions known.
- · Dangerous decomposition products: No dangerous decomposition products known.

17.00 %

250.0 g/l

## 11 Toxicological information

· Acute toxicity:

Г	· LD/LC50 1	· LD/LC50 values relevant for classification:		
	100-42-5 Styrene			
	Oral	LD50	5000 mg/kg (rat)	
	Inhalative	LC50/4 h	24 mg/l (rat)	

(Contd. on page 5)



Printing date 26.08.2010 Revision: 26.08.2010

Trade name: Dinitrol 6085 Faserfeinspachtel hell

(Contd. of page 4)

- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Harmful Irritant

- · Inhalation: Harmful by inhalation.
- · Ingestion: May cause similar symptoms as for inhalation.

### 12 Ecological information

- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

### 13 Disposal considerations

- · Product:
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · European waste catalogue
- 08 00 00 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS

08 04 00 wastes from MFSU of adhesives and sealants (including waterproofing products)

08 04 09 waste adhesives and sealants containing organic solvents or other dangerous substances

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

#### 14 Transport information

· Land transport ADR/RID (cross-border)



· ADR/RID class: 3 Flammable liquids.

· Danger code (Kemler): · UN-Number: 3269
· Packaging group: III
· Hazard label 3

· Description of goods: 3269 POLYESTER RESIN KIT

· Limited quantities (LQ) LQ7

(Contd. on page 6)



Printing date 26.08.2010 Revision: 26.08.2010

Trade name: Dinitrol 6085 Faserfeinspachtel hell

(Contd. of page 5)

- · Transport category
- · Tunnel restriction code E
- · Maritime transport IMDG:



· IMDG Class: · UN Number: 3269 · Label 3 · Packaging group: III· EMS Number: F-E,S-D· Marine pollutant:

· Proper shipping name: POLYESTER RESIN KIT

No

· Air transport ICAO-TI and IATA-DGR:



· ICAO/IATA Class: · UN/ID Number: 3269 · Label 3 III· Packaging group:

· Proper shipping name: POLYESTER RESIN KIT

### 15 Regulatory information

· Labelling according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· Code letter and hazard designation of product:



Xn Harmful

· Hazard-determining components of labelling:

Styrene

· Risk phrases:

Flammable.

Harmful by inhalation.

36/38 Irritating to eyes and skin.

- · Safety phrases:
- 2 Keep out of the reach of children.
- 9 Keep container in a well-ventilated place.
- 13 Keep away from food, drink and animal feedingstuffs.
- 23 Do not breathe fumes/aerosol.
- 46 If swallowed, seek medical advice immediately and show this container or label.

(Contd. on page 7)



Printing date 26.08.2010 Revision: 26.08.2010

Trade name: Dinitrol 6085 Faserfeinspachtel hell

(Contd. of page 6)

56 Dispose of this material and its container to hazardous or special waste collection point.

- · National regulations:
- · Information about limitation of use: Employment restrictions concerning juveniles must be observed.
- · Technical instructions (air):

Class	Share in %
NK	10-25

· Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.

· EU-VOC: 17.04 %

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant R-phrases

10 Flammable.

20 Harmful by inhalation.

36/38 Irritating to eyes and skin.

38 Irritating to skin.

51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

- · Department issuing MSDS: Research & Development
- · Contact: Dr. Thomas Sürig
- \* Data compared to the previous version altered.

GB