



Material Safety Data Sheet

2K Epoxy Primer Black

1. Product and company identification

Product name : 2K Epoxy Primer Black

Manufactured For:

The Easthill Group Dba/The Eastwood Company

263 Shoemaker Road

Pottstown, PA 19464

USA & Canada: 800-345-1178

Outside USA: 610-323-2200

Emergency contact: Chem-Trec: 800-424-9300

2. Hazards identification

Physical state : Liquid. [Aerosol.]

Odor : Characteristic.

Emergency overview

Signal word : DANGER!

Hazard statements : FLAMMABLE AEROSOL. HARMFUL IF INHALED. INHALATION CAUSES HEADACHES, DIZZINESS, DROWSINESS AND NAUSEA AND MAY LEAD TO UNCONSCIOUSNESS. CAUSES RESPIRATORY TRACT, EYE AND SKIN IRRITATION. MAY CAUSE ALLERGIC SKIN REACTION. MAY BE HARMFUL IF ABSORBED THROUGH SKIN OR IF SWALLOWED. CONTAINS MATERIAL THAT MAY CAUSE TARGET ORGAN DAMAGE, BASED ON ANIMAL DATA. POSSIBLE CANCER HAZARD - CONTAINS MATERIAL WHICH MAY CAUSE CANCER, BASED ON ANIMAL DATA. POSSIBLE DEVELOPMENTAL HAZARD - CONTAINS MATERIAL WHICH MAY CAUSE ADVERSE DEVELOPMENTAL EFFECTS, BASED ON ANIMAL DATA.

Precautions : Do not puncture, incinerate or store the container at temperatures above 120°F (49°C) or in direct sunlight. Avoid exposure - obtain special instructions before use. Do not breathe vapor or mist. Do not ingest. Do not get in eyes or on skin or clothing. Avoid exposure during pregnancy. Use only with adequate ventilation. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling.

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Routes of entry : Dermal contact. Eye contact. Inhalation. Ingestion.

Potential acute health effects

Inhalation : Toxic by inhalation. Can cause central nervous system (CNS) depression. Irritating to respiratory system.

Ingestion : Harmful if swallowed. Can cause central nervous system (CNS) depression.

Skin : Harmful in contact with skin. Irritating to skin. Defatting to the skin. May cause sensitization by skin contact.

Eyes : Severely irritating to eyes. Risk of serious damage to eyes.

Potential chronic health effects

2. Hazards identification

- Chronic effects** : Contains material that may cause target organ damage, based on animal data. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.
- Carcinogenicity** : Contains material which may cause cancer, based on animal data. Risk of cancer depends on duration and level of exposure.
- Mutagenicity** : No known significant effects or critical hazards.
- Teratogenicity** : No known significant effects or critical hazards.
- Developmental effects** : Contains material which may cause developmental abnormalities, based on animal data.
- Fertility effects** : No known significant effects or critical hazards.
- Target organs** : Contains material which may cause damage to the following organs: blood, kidneys, lungs, the nervous system, liver, spleen, lymphatic system, gastrointestinal tract, upper respiratory tract, skin, bone marrow, central nervous system (CNS), ears, eye, lens or cornea.

Over-exposure signs/symptoms

- Inhalation** : Adverse symptoms may include the following:
nausea or vomiting
respiratory tract irritation
coughing
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
reduced fetal weight
increase in fetal deaths
- Ingestion** : Adverse symptoms may include the following:
reduced fetal weight
increase in fetal deaths
- Skin** : Adverse symptoms may include the following:
irritation
redness
dryness
cracking
reduced fetal weight
increase in fetal deaths
- Eyes** : Adverse symptoms may include the following:
pain or irritation
watering
redness
reduced fetal weight
increase in fetal deaths
- Medical conditions aggravated by over-exposure** : Pre-existing skin disorders and disorders involving any other target organs mentioned in this MSDS as being at risk may be aggravated by over-exposure to this product.

3. Composition/information on ingredients

Name	CAS number	%
dimethyl ether	115-10-6	15-40
acetone	67-64-1	10-30
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin	25068-38-6	5-10
xylene	1330-20-7	1-5
5-methylhexan-2-one	110-12-3	1-5
trizinc bis(orthophosphate)	7779-90-0	1-5
Hydrocarbons, C10, aromatics, <1% naphthalene	64742-94-5	1-5
2-butoxyethanol	111-76-2	1-5
butan-1-ol	71-36-3	0.5-1.5
ethylbenzene	100-41-4	0.5-1.5

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

4. First aid measures

Eye contact	: Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention immediately.
Skin contact	: In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention immediately.
Inhalation	: Move exposed person to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention immediately.
Ingestion	: Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.
Notes to physician	: No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

5. Fire-fighting measures

Flammability of the product : Flammable aerosol. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion. Bursting aerosol containers may be propelled from a fire at high speed. Runoff to sewer may create fire or explosion hazard.

Extinguishing media

Suitable :

5. Fire-fighting measures

- In case of fire, use water spray. Powder. CO₂. LARGE FIRE: Use alcohol-resistant foam or water spray or fog. Cool closed containers exposed to fire with water.
- Not suitable** : Do not use water jet.
- Special exposure hazards** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- Hazardous thermal decomposition products** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
phosphorus oxides
halogenated compounds
metal oxide/oxides
Hydrocarbon.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.
- Special remarks on explosion hazards** : Air/vapor mixtures may be explosive.

6. Accidental release measures

- Personal precautions** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. In the case of aerosols being ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant. If a large number of containers are ruptured, treat as a bulk material spillage according to the instructions in the clean-up section. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
- Methods for cleaning up**
- Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

7. Handling and storage

- Handling** : Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Avoid exposure during pregnancy. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Avoid breathing gas. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use non-sparking tools. Empty containers retain product residue and can be hazardous.
- Storage** : Do not store above the following temperature: 50°C (122°F). Store in accordance with local regulations. Store in a segregated and approved area. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Use appropriate containment to avoid environmental contamination.

8. Exposure controls/personal protection

United States

Ingredient	Exposure limits
dimethyl ether	AIHA WEEL (United States, 10/2011). TWA: 1000 ppm 8 hours.
acetone	ACGIH TLV (United States, 3/2012). TWA: 500 ppm 8 hours. TWA: 1188 mg/m ³ 8 hours. STEL: 750 ppm 15 minutes. STEL: 1782 mg/m ³ 15 minutes. OSHA PEL 1989 (United States, 3/1989). TWA: 750 ppm 8 hours. TWA: 1800 mg/m ³ 8 hours. STEL: 1000 ppm 15 minutes. STEL: 2400 mg/m ³ 15 minutes. NIOSH REL (United States, 1/2013). TWA: 250 ppm 10 hours. TWA: 590 mg/m ³ 10 hours. OSHA PEL (United States, 6/2010). TWA: 1000 ppm 8 hours. TWA: 2400 mg/m ³ 8 hours.
xylene	ACGIH TLV (United States, 3/2012). TWA: 100 ppm 8 hours. TWA: 434 mg/m ³ 8 hours. STEL: 150 ppm 15 minutes. STEL: 651 mg/m ³ 15 minutes. OSHA PEL 1989 (United States, 3/1989). TWA: 100 ppm 8 hours. TWA: 435 mg/m ³ 8 hours. STEL: 150 ppm 15 minutes. STEL: 655 mg/m ³ 15 minutes. OSHA PEL (United States, 6/2010). TWA: 100 ppm 8 hours. TWA: 435 mg/m ³ 8 hours.
5-methylhexan-2-one	ACGIH TLV (United States, 3/2012). TWA: 50 ppm 8 hours. TWA: 234 mg/m ³ 8 hours. OSHA PEL 1989 (United States, 3/1989). TWA: 50 ppm 8 hours. TWA: 240 mg/m ³ 8 hours.

8. Exposure controls/personal protection

trizinc bis(orthophosphate)	NIOSH REL (United States, 1/2013). TWA: 50 ppm 10 hours. TWA: 240 mg/m³ 10 hours. OSHA PEL (United States, 6/2010). TWA: 100 ppm 8 hours. TWA: 475 mg/m³ 8 hours. ACGIH TLV (United States). TWA: 10 mg/m³ Form: Inhalable TWA: 3 mg/m³ Form: Respirable fraction
Hydrocarbons, C10, aromatics, <1% naphthalene	ACGIH TLV (United States, 2/2010). Absorbed through skin. TWA: 200 mg/m³, (as total hydrocarbon vapor) 8 hours.
2-butoxyethanol	OSHA PEL 1989 (United States, 3/1989). Absorbed through skin. TWA: 25 ppm 8 hours. TWA: 120 mg/m³ 8 hours. NIOSH REL (United States, 1/2013). Absorbed through skin. TWA: 5 ppm 10 hours. TWA: 24 mg/m³ 10 hours. ACGIH TLV (United States, 3/2012). TWA: 20 ppm 8 hours. OSHA PEL (United States, 6/2010). Absorbed through skin. TWA: 50 ppm 8 hours. TWA: 240 mg/m³ 8 hours.
butan-1-ol	ACGIH TLV (United States, 3/2012). TWA: 20 ppm 8 hours. OSHA PEL 1989 (United States, 3/1989). Absorbed through skin. CEIL: 50 ppm CEIL: 150 mg/m³ NIOSH REL (United States, 1/2013). Absorbed through skin. CEIL: 50 ppm CEIL: 150 mg/m³ OSHA PEL (United States, 6/2010). TWA: 100 ppm 8 hours. TWA: 300 mg/m³ 8 hours.
ethylbenzene	ACGIH TLV (United States, 3/2012). TWA: 20 ppm 8 hours. OSHA PEL 1989 (United States, 3/1989). TWA: 100 ppm 8 hours. TWA: 435 mg/m³ 8 hours. STEL: 125 ppm 15 minutes. STEL: 545 mg/m³ 15 minutes. NIOSH REL (United States, 1/2013). TWA: 100 ppm 10 hours. TWA: 435 mg/m³ 10 hours. STEL: 125 ppm 15 minutes. STEL: 545 mg/m³ 15 minutes. OSHA PEL (United States, 6/2010). TWA: 100 ppm 8 hours. TWA: 435 mg/m³ 8 hours.

Recommended monitoring procedures : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Engineering measures : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

8. Exposure controls/personal protection

Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Personal protection	
Respiratory	: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Recommended: If operating conditions cause high vapor concentrations or the TLV is exceeded, use supplied-air respirator. half-face mask (as filter combination A1P2)
Hands	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. Recommended: Nitrile gloves. Short term exposure (15 min.): Butyl rubber gloves. (0.7 mm)
Eyes	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
Skin	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

9. Physical and chemical properties

Physical state	: Liquid. [Aerosol.]
Flash point	: <0°C (<32°F) [without propellant]
Auto-ignition temperature	: 235°C (455°F)
Flammable limits	: Lower: 2.6% Upper: 18.6%
Odor	: Characteristic.
Vapor pressure	: 340 kPa (2550.2 mm Hg) [room temperature]
VOC content	: 64.49%
Viscosity	: Not available.
Solubility	: Insoluble in the following materials: cold water and hot water.

10. Stability and reactivity

- Chemical stability** : The product is stable.
- Conditions to avoid** : Avoid all possible sources of ignition (spark or flame).
Keep away from heat and direct sunlight.
- Incompatible materials** : Reactive or incompatible with the following materials: oxidizing materials, acids and alkalis.
- Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.
- Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.

Under normal conditions of storage and use, hazardous polymerization will not occur.

11. Toxicological information

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
dimethyl ether	LC50 Inhalation Gas.	Rat	164000 ppm	4 hours
	LC50 Inhalation Vapor	Rat	309 g/m ³	4 hours
acetone	LD50 Dermal	Rabbit	20000 mg/kg	-
	LD50 Oral	Rat	5800 mg/kg	-
xylene	LC50 Inhalation Gas.	Rat	5000 ppm	4 hours
	LD50 Dermal	Rabbit	2000 mg/kg	-
	LD50 Oral	Rat	4300 mg/kg	-
5-methylhexan-2-one	LC50 Inhalation Vapor	Rat	3813 ppm	4 hours
	LD50 Oral	Rat	3200 mg/kg	-
trizinc bis(orthophosphate)	LD50 Oral	Rat	>5000 mg/kg	-
Hydrocarbons, C10, aromatics, <1% naphthalene	LC50 Inhalation Dusts and mists	Rat	>5 mg/l	4 hours
	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
2-butoxyethanol	LC50 Inhalation Dusts and mists	Rat	2175 mg/m ³	4 hours
	LC50 Inhalation Vapor	Rat	450 ppm	4 hours
	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat	560 mg/kg	-
butan-1-ol	LC50 Inhalation Vapor	Rat	24000 mg/m ³	4 hours
	LD50 Dermal	Rabbit	3400 mg/kg	-
	LD50 Oral	Rat	790 mg/kg	-
ethylbenzene	LC50 Inhalation Vapor	Rat	17.2 mg/l	4 hours
	LD50 Dermal	Rabbit	15354 mg/kg	-
	LD50 Oral	Rat	3500 mg/kg	-

Chronic toxicity

Not available.

Irritation/Corrosion

11. Toxicological information

Product/ingredient name	Result	Species	Score	Exposure	Observation
acetone	Eyes - Moderate irritant	Rabbit	-	24 hours 20 milligrams	-
	Eyes - Severe irritant	Rabbit	-	20 milligrams	-
	Skin - Mild irritant	Rabbit	-	24 hours 500 milligrams	-
	Skin - Mild irritant	Rabbit	-	395 milligrams	-
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin	Eyes - Mild irritant	Rabbit	-	100 milligrams	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 microliters	-
	Skin - Severe irritant	Rabbit	-	24 hours 2 milligrams	-
xylene	Eyes - Mild irritant	Rabbit	-	87 milligrams	-
	Eyes - Severe irritant	Rabbit	-	24 hours 5 milligrams	-
	Skin - Mild irritant	Rat	-	8 hours 60 microliters	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 milligrams	-
5-methylhexan-2-one	Skin - Moderate irritant	Rabbit	-	100 Percent	-
	Eyes - Mild irritant	Rabbit	-	24 hours 100 microliters	-
Hydrocarbons, C10, aromatics, <1% naphthalene 2-butoxyethanol	Skin - Mild irritant	Rabbit	-	24 hours 500 microliters	-
	Eyes - Moderate irritant	Rabbit	-	24 hours 100 milligrams	-
	Eyes - Severe irritant	Rabbit	-	100 milligrams	-
	Skin - Mild irritant	Rabbit	-	500 milligrams	-
butan-1-ol	Eyes - Severe irritant	Rabbit	-	24 hours 2 milligrams	-
	Eyes - Severe irritant	Rabbit	-	0.005 Milliliters	-
	Skin - Moderate irritant	Rabbit	-	24 hours 20 milligrams	-
ethylbenzene	Eyes - Severe irritant	Rabbit	-	500 milligrams	-
	Skin - Mild irritant	Rabbit	-	24 hours 15 milligrams	-

: Not available.

Sensitizer

Product/ingredient name	Route of exposure	Species	Result
acetone	skin	Guinea pig	Not sensitizing
Hydrocarbons, C10, aromatics, <1% naphthalene	skin	Guinea pig	Not sensitizing

Carcinogenicity

Classification

11. Toxicological information

Product/ingredient name	ACGIH	IARC	EPA	NIOSH	NTP	OSHA
acetone	A4	-	-	-	-	-
xylene	A4	3	-	-	-	-
2-butoxyethanol	A3	3	-	-	-	-
ethylbenzene	A3	2B	-	-	-	-

Mutagenicity

Product/ingredient name	Test	Experiment	Result
acetone	476 <i>In vitro</i> Mammalian Cell Gene Mutation Test	Experiment: <i>In vitro</i> Subject: Mammalian-Animal	Negative
	471 Bacterial Reverse Mutation Test	Subject: Bacteria	Negative
xylene	471 Bacterial Reverse Mutation Test	Subject: Bacteria	Negative

Teratogenicity

Not available.

Conclusion/Summary : Xylene: May cause developmental abnormalities, based on animal data.

Reproductive toxicity

Not available.

12. Ecological information

Ecotoxicity : This material is very toxic to aquatic life. This material is toxic to aquatic life with long lasting effects.

Aquatic ecotoxicity

Product/ingredient name	Result	Species	Exposure
acetone	Acute EC50 20.565 mg/l Marine water Acute LC50 6000000 µg/l Fresh water Acute LC50 10000 µg/l Fresh water Acute LC50 100 mg/l Fresh water	Algae - <i>Ulva pertusa</i> Crustaceans - <i>Gammarus pulex</i> Daphnia - <i>Daphnia magna</i> Fish - <i>Pimephales promelas</i> - Juvenile (Fledgling, Hatchling, Weanling)	96 hours 48 hours 48 hours 96 hours
	Chronic NOEC 4.95 mg/l Marine water Chronic NOEC 0.016 ml/L Fresh water Chronic NOEC 0.1 ml/L Fresh water	Algae - <i>Ulva pertusa</i> Crustaceans - Daphniidae Daphnia - <i>Daphnia magna</i> - Neonate	96 hours 21 days 21 days
xylene	Acute IC50 2.2 mg/l Acute LC50 8500 µg/l Marine water	Algae Crustaceans - <i>Palaemonetes pugio</i>	72 hours 48 hours
	Acute LC50 13400 µg/l Fresh water Acute LC50 159000 µg/l Fresh water Acute LC50 90 µg/l Fresh water Acute EC50 1 to 10 mg/l	Fish - <i>Pimephales promelas</i> Fish - <i>Pimephales promelas</i> Fish - <i>Oncorhynchus mykiss</i> Daphnia	96 hours 96 hours 96 hours 48 hours
5-methylhexan-2-one trizinc bis(orthophosphate) Hydrocarbons, C10, aromatics, <1% naphthalene	Acute IC50 1 to 10 mg/l Acute LC50 1 to 10 mg/l	Algae Fish	72 hours 96 hours

12. Ecological information

2-butoxyethanol	Acute EC50 1550 mg/l Acute LC50 1000 mg/l Marine water	Daphnia - Daphnia magna Crustaceans - Chaetogammarus marinus - Young	48 hours 48 hours
butan-1-ol	Acute LC50 1250000 µg/l Marine water Acute NOEC 100 mg/l	Fish - Menidia beryllina Daphnia - Daphnia magna	96 hours 21 days
ethylbenzene	Acute EC50 1983000 µg/l Fresh water Acute LC50 1730000 µg/l Fresh water Acute EC50 4.6 mg/l Acute EC50 3600 µg/l Fresh water	Daphnia - Daphnia magna Fish - Pimephales promelas Algae - chneriella subcapitata Algae - Pseudokirchneriella subcapitata	48 hours 96 hours 72 hours 96 hours
	Acute EC50 2.1 mg/l Acute LC50 5200 µg/l Marine water	Daphnia - Daphnia Magna Crustaceans - Americamysis bahia	48 hours 48 hours
	Acute LC50 4200 µg/l Fresh water Chronic NOEC 1000 µg/l Fresh water	Fish - Oncorhynchus mykiss Algae - Pseudokirchneriella subcapitata	96 hours 96 hours

Persistence/degradability

Product/ingredient name	Test	Result	Dose	Inoculum
acetone	OECD 301B Ready Biodegradability - CO ₂ Evolution Test	91 % - 28 days	-	-
Hydrocarbons, C10, aromatics, <1% naphthalene	OECD 301F Ready Biodegradability - Manometric Respirometry Test	49.56 % - 28 days	-	-
2-butoxyethanol	OECD 302B Inherent Biodegradability: Zahn-Wellens/ EMPA Test	99 % - 28 days	-	-
	OECD 301E Ready Biodegradability - Modified OECD Screening Test	95 % - 28 days	-	-

13. Disposal considerations

Waste disposal : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

13. Disposal considerations

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

14. Transport information

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
DOT Classification	UN1950	Aerosols RQ(xylene, acetone)	2.1	-		Reportable quantity 2410.8 lbs / 1094.5 kg Package sizes shipped in quantities less than the product reportable quantity are not subject to the RQ (reportable quantity) transportation requirements. Packaging instruction Passenger aircraft Quantity limitation: 75 kg Cargo aircraft Quantity limitation: 150 kg Special provisions N82
IMDG Class	UN1950	AEROSOLS. Marine pollutant (trizinc bis (orthophosphate), Hydrocarbons, C10, aromatics, <1% naphthalene)	2.1	-	 	Emergency schedules (EmS) F-D, S-U
IATA-DGR Class	UN1950	Aerosols, flammable	2.1	-		Passenger and Cargo AircraftQuantity limitation: 75 kg Packaging instructions: 203 Cargo Aircraft Only Quantity limitation: 150 kg Packaging instructions: 203 Limited Quantities - Passenger AircraftQuantity limitation: 30 kg Packaging instructions: Y203

PG* : Packing group

15. Regulatory information

HCS Classification : Flammable aerosol
Toxic material
Irritating material
Sensitizing material
Carcinogen
Target organ effects

15. Regulatory information

- U.S. Federal regulations :
- TSCA 8(a) PAIR: 5-methylhexan-2-one
 - TSCA 8(a) CDR Exempt/Partial exemption: Not determined
 - United States inventory (TSCA 8b): Not determined.
 - TSCA 12(b) one-time export: 5-methylhexan-2-one
 - SARA 302/304: ethylenediamine
 - SARA 311/312 Hazards identification: Fire hazard, Immediate (acute) health hazard, Delayed (chronic) health hazard
 - Clean Water Act (CWA) 307: trizinc bis(orthophosphate); ethylbenzene; zinc oxide
 - Clean Water Act (CWA) 311: xylene; ethylbenzene; ethylenediamine
 - Clean Air Act (CAA) 112 accidental release prevention: No products were found.
 - Clean Air Act (CAA) 112 regulated flammable substances: dimethyl ether
- Clean Air Act Section 112 : Listed
(b) Hazardous Air Pollutants (HAPs)
- Clean Air Act Section 602 : Not listed
Class I Substances
- Clean Air Act Section 602 : Not listed
Class II Substances
- DEA List I Chemicals : Not listed
(Precursor Chemicals)
- DEA List II Chemicals : Listed
(Essential Chemicals)

SARA 313

	Product name	CAS number	Concentration
Form R - Reporting requirements	xylene	1330-20-7	1-5
	trizinc bis(orthophosphate)	7779-90-0	1-5
	2-butoxyethanol	111-76-2	1-5
	butan-1-ol	71-36-3	1-5
	ethylbenzene	100-41-4	1-5
Supplier notification	xylene	1330-20-7	1-5
	trizinc bis(orthophosphate)	7779-90-0	1-5
	2-butoxyethanol	111-76-2	1-5
	butan-1-ol	71-36-3	1-5
	ethylbenzene	100-41-4	1-5

SARA 313 notifications must not be detached from the MSDS and any copying and redistribution of the MSDS shall include copying and redistribution of the notice attached to copies of the MSDS subsequently redistributed.

State regulations

- Massachusetts : The following components are listed: XYLENE; METHYL ISOAMYL KETONE; 2-BUTOXYETHANOL; ETHYL BENZENE; METHYL ETHER; ACETONE; N-BUTYL ALCOHOL
- New York : The following components are listed: Xylene (mixed); Ethylbenzene; Acetone; 2-Propanone; Butyl alcohol; 1-Butanol
- New Jersey : The following components are listed: XYLENES; BENZENE, DIMETHYL-; METHYL ISOAMYL KETONE; 2-HEXANONE, 5-METHYL-; ZINC compounds; 2-BUTOXY ETHANOL; BUTYL CELLOSOLVE; ETHYL BENZENE; BENZENE, ETHYL-; DIMETHYL ETHER; METHANE, OXYBIS-; ACETONE; 2-PROPANONE; n-BUTYL ALCOHOL; 1-BUTANOL

15. Regulatory information

Pennsylvania : The following components are listed: BENZENE, DIMETHYL-; 2-HEXANONE, 5-METHYL-; ZINC COMPOUNDS; ETHANOL, 2-BUTOXY-; BENZENE, ETHYL-; METHANE, OXYBIS-; 2-PROPANONE; 1-BUTANOL

California Prop. 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

Ingredient name	Cancer	Reproductive	No significant risk level	Maximum acceptable dosage level
ethylbenzene	Yes.	No.	41 µg/day (ingestion) 54 µg/day (inhalation)	No.

United States inventory (TSCA 8b) : Not determined.

Canada inventory : Not determined.

International regulations

International lists : **Australia inventory (AICS):** Not determined.
China inventory (IECSC): Not determined.
Japan inventory: Not determined.
Korea inventory: Not determined.
Malaysia Inventory (EHS Register): Not determined.
New Zealand Inventory of Chemicals (NZIoC): Not determined.
Philippines inventory (PICCS): Not determined.
Taiwan inventory (CSNN): Not determined.

Chemical Weapons Convention List Schedule I Chemicals : Not listed

Chemical Weapons Convention List Schedule II Chemicals : Not listed

Chemical Weapons Convention List Schedule III Chemicals : Not listed

16. Other information

Label requirements : FLAMMABLE AEROSOL. HARMFUL IF INHALED. INHALATION CAUSES HEADACHES, DIZZINESS, DROWSINESS AND NAUSEA AND MAY LEAD TO UNCONSCIOUSNESS. CAUSES RESPIRATORY TRACT, EYE AND SKIN IRRITATION. MAY CAUSE ALLERGIC SKIN REACTION. MAY BE HARMFUL IF ABSORBED THROUGH SKIN OR IF SWALLOWED. CONTAINS MATERIAL THAT MAY CAUSE TARGET ORGAN DAMAGE, BASED ON ANIMAL DATA. POSSIBLE CANCER HAZARD - CONTAINS MATERIAL WHICH MAY CAUSE CANCER, BASED ON ANIMAL DATA. POSSIBLE DEVELOPMENTAL HAZARD - CONTAINS MATERIAL WHICH MAY CAUSE ADVERSE DEVELOPMENTAL EFFECTS, BASED ON ANIMAL DATA.

16. Other information

Hazardous Material :
Information System (U.S.A.)

Health	*	2
Flammability		4
Physical hazards		0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

National Fire Protection :
Association (U.S.A.)



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

Date of issue : 9/13/2013.
Date of previous issue : No previous validation.
Version : 1

Indicates information that has changed from previously issued version.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.