MATERIAL SAFETY DA	Hazard Co	mmunication	Standard,	29 CFR 1910	.1200.	=== 0
PRODUCT NUMBER:514		Revision Date: 05/20/2009				
Section I						
anufactured For: The Eastwoo ddress: 263 Shoemak Pottstown, Outside USA		aker Rd.	Emergency: 1-800-434-9300(Chem- Information:US & Cana			
HMIS CODES: REACTIV Section II: HAZAR ingredients contai	DOUS INGRE	DIENTS/IDEN	TITY INFORM	ATION (All	of the	
Name		Cas No.	OSHA PEL	ACGIH TLV	OTHER LIM	%
2-BUTOXY ETHANOL ACETONE DIETHYLENE GLYCOL ISOPROPYL ALCOHOL PROPANE/N-BUTANE Comment: THIS PRODUCT CON		68476-86-8	1000 PPM N/A 400 PPM 1000 PPM	200 PPM 600 PPM WITH AN *	N/A	
TO THE REPORTING AND COMMUNITY RI					CTTEANNING	
Section III: PHYS						
Boiling Point: Vapor Pressure(mm Vapor Density(AIR= Solubility in Wate Appearance and Odo	Hg) N. 1) >:	/D Spec /D Melt 1 Evap	cific Gravi ting Point: poration Ra tyl Acetate	ty (water=1 te: =1)		
Section IV: FIRE		ION HAZARD I				
Flash Point (Method					====================================	-= == 0

Extinguishing Media: STANDARD DRY CHEMICAL FIRE EXTINGUISHER Special Fire Fighting Procedures: WEAR SELF CONTAINED BREATHING APPARATUS.

Unusual Fire and Explosion Hazards: FLAMMABLE. CONTENTS UNDER PRESSURE. DO NOT PUNCTURE OR INCINERATE CONTAINER. KEEP AWAY FROM HEAT OR TEMPERATURES ABOVE 120 F. EXPOSURE TO TEMPERATURES ABOVE 120F MAY CAUSE CAN TO BURST.

Section V: REACTIVITY DATA

PRODUCT NUMBER: 51482

Stability: Unstable: Conditions to avoid: Stable: X TEMPERATURES ABOVE 120F

Incompatability (Materials to Avoid): AVOID ALKALIS AND STRONG OXIDIZERS.

KEEP AWAY FROM HEAT AND OPEN FLAME.

Hazardous Decomposition or Byproducts: CARBON MONOXIDE, CARBON DIOXIDE.

Hazardous Polymerization: May Occur: Will Not Occur: X

Conditions to Avoid: N/A

Section VI: HEALTH HAZARD DATA

Routes of Entry: Inhalation: YES Skin: YES Ingestion: YES

Health Hazards (Acute and Chronic):

EYES: SEVERE IRRITATION OR BURNING. SKIN: SEVERE IRRITATION, LOCALIZED DEFATTING. INHALATION: SEVERE IRRITATION TO EYES, NOSE AND RESPIRATORY TRACT. INGESTION: NAUSEA, STOMACH UPSET, VOMITING.

Carcinogenicity: NTP:NO IARC Monographs:NO OSHA Reg:NO

Signs and Symptoms of Exposure: SEE HEALTH HAZARDS ABOVE

Medical Conditions Generally Aggravated by Exposure: EXCESSIVE EXPOSURE WILL AGGRAVATE RESPIRATORY, CARDIOVASCULAR OR PULMONARY ILLNESSES.

Emergency and First Aid Procedures: INHALATION: REMOVE TO FRESH AIR.CONSULT PHYSICIAN IF DIFFICULTY IN BREATHING PERSISTS. EYES: FLUSH WITH WATER FOR 15 MINUTES. CONSULT PHYSICIAN. SKIN: WASH AREA WITH SOAP AND WATER. INGESTION: CONSULT PHYSICAN.

Section VII: PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be Taken in Case Material is Released or Spilled: WIPE UP SMALL SPILL WITH TOWEL AND ALLOW AREA TO DRY. EXCESS MAY BE REMOVED AFTER DRYING WITH SANDPAPER OR OTHER SCRAPING DEVICE. DISPOSE OF RESIDUE IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL GUIDELINES.

Waste Disposal Method: WRAP CONTAINER AND PLACE IN TRASH COLLECTION. DO NOT PUNCTURE OR INCINERATE CONTAINER.

Precautions to be Taken in Handling and Storing: STORE IN A COOL DRY AREA. KEEP AWAY FROM HEAT OR OPEN FLAMES.

Other Precautions: TEMPERATURES ABOVE 120 F MAY CAUSE BURSTING.

Section VIII: CONTROL MEASURES

Respiratory Protection: USE ONLY IN A WELL VENTILATED AREA.

Ventilation: Local Exhaust:ADEQUATE

Mechanical: N/A Special: N/A

Other: N/A

Protective Gloves: CHEMICAL RESISTANT

Eye Protection: SAFETY GLASSES ARE RECOMMENDED WHENEVER CHEMICALS ARE USED.

Other Protective Clothing or Equipment:

IF EXPOSURE LIMITS ARE EXCEEDED WEAR A NIOSH APPROVED RESPIRATOR.

Work/Hygienic Practices: WASH HANDS AFTER USE.